



Sound absorbing line

POLYWALL NLS DRAW

Low-cost customization and high sound absorption

ADVANTAGES

- Low cost
- High sound absorption
- Versatility of use
- Customization

DESCRIPTION

Polyester fiber panel in black color screen printed on one side in Euroclass B, s2-d0 with excellent sound absorbing properties, designed for the visible treatments of particularly noisy and reverberating places such as bars, restaurants, theaters, cinemas, schools, conservatories, public places in general. Its faces are specially worked on the surface to make them even more pleasant to the eye and prevent the deposit of dust and dirt in general.

SIZE

Thickness	mm	40 mm
Format	Panel	59,5 x 59,5 cm
Packaging	Piece	26
Weight	Kg/mq	0,57 Kg/mq



TECHNICAL INFORMATION

Densità [ρ]		40 Kg/mq
Sound absorption coefficient [α_w]	UNI EN ISO 354	0,7
Fire classification [Class]	EN 13501-1	B, s2-d0
Reaction to fire [Class]	UNI 9177 UNI 8457 UNI 9174	1
Impact resistance with Magnetic Kit	DIN 18032	EXCEEDED
Volatile organic compound (TVOC) emission	UNI EN ISO 16000 - 9	CLASSE A+

DOP

POLYMAXITALIA SRL headquartered in Via Fusina no. 12 of Castelfranco Veneto, a company operating in the production and marketing of materials and systems for the acoustic insulation of buildings and subjected to quality control ISO 9001, with reference to European Regulation 305/2011 (ex Directive 89/106), regulating the performance of construction products, in force since 1 year. July 2013:

“in the absence of harmonised European standards for products with a sound insulation function, result in performance dependent not on the individual product but on a combination of components and the basic building system”,

DECLARES

than for the product POLYWALL NLS DRAW sp. 40 mm, is not bound to the certification process aimed at the production of the declaration of performance.

In this regard, the data reported in the relevant product fiche are authentic.

