

Accessories Floor Line

FASCIA POLYCELL 22



THE INTERNATIONAL EPD®
S-P-05219 www.env

DESCRIPTION

Adhesive perimeter tape (AD) in extruded polyethylene foam density 22 Kg/ mc, with controlled and constant density. This product is suitable for de-solidation of the screed and floor from vertical partitions, preventing the creation of harmful acoustic bridges. The product must be laid continuously without interruption and the excess tape should be cut only after the final coating is laid. This type of band is also available in non-adhesive version (N).

SIZE - AD/N

Thickness	Format - Roll	Packaging - Lots	Height
3 mm	0,10 x 100 m	1500 ml	10 cm
5 mm	0,10 x 100 m	1500 ml	
8 mm	0,10 x 60 m	900 ml	
10 mm	0,10 x 50 m	750 ml	
3 mm	0,10 x 100 m	1000 ml	15 cm
5 mm	0,10 x 100 m	1000 ml	
8 mm	0,10 x 60 m	600 ml	
10 mm	0,10 x 50 m	500 ml	
3 mm	0,10 x 100 m	700 ml	20 cm
5 mm	0,10 x 100 m	700 ml	
8 mm	0,10 x 60 m	420 ml	
10 mm	0,10 x 50 m	350 ml	



TECHNICAL INFORMATION - AD/N

Volatile organic compound (TVOC) emission

UNI EN ISO 16000-9

Classe A+

DOP

POLYMAXITALIA SRL headquartered in Via Fusina n° 12 of Castelfranco Veneto, a company operating in the production and marketing of materials and systems for the acoustic insulation of buildings and subjected to quality control ISO 9001, with reference to European Regulation 305/2011 (ex Directive 89/106), regulating the performance of construction products, in force since 1 year. July 2013:

“in the absence of harmonised European standards for products with a sound insulation function, result in performance dependent not on the individual product but on a combination of components and the basic building system”,

DECLARES

than for the product POLYCELL 22 AD/N sp. 3-5-8-10 mm,s not bound to the certification process aimed at the production of the declaration of performance.

In this regard, the data reported in the relevant product fiche are authentic.

LAYING SCHEME

Apply the **POLYCELL 22 AD/N** continuously on the entire perimeter of the rooms to be treated; detach the protective film from the adhesive vertical part of the band and fix it to the base of the wall (only for the adhesive version “AD”).

Special attention should be paid to the continuous drawing of **POLYCELL 22 AD/N** at sensitive points (corners, doors, thresholds etc.).

Emanuele Bonifazi
Responsabile Direzione Tecnica

