

ChovACUSTIC® 35 FIELTEX

CÓD. 56304

DESCRIPTION

Multilayer compound formed by a textile felt of 16 mm. thermally adhered to a high density sheet of 2mm.

Excellent and versatile device to reduce the air noise transmission in a wide frequency range, thanks to:

- High density and elasticity (viscoelastic sheet).
- High-porosity (textile felt).



INSTALLATION

- 1- Cut a section of **ChovACUSTIC®** taking into account the downspout dimension. To do this, use a cutter or radial saw.
- 2- Wrap the downspout with **ChovACUSTIC®** facing the viscoelastic sheet. Ensure the material by plastic flanges placed every 20 cm.
- 3- Repeat these steps, placing contiguously the various sections.
- 4- Place **ChovASEAL** adhesive sealing tape at all joints to ensure seal.



ChovACUSTIC® 35 FIELTEX

THECNICAL SPECIFICATIONS

THICKNESS (mm)	18
AVERAGE WEIGHT (kg/m ²)	4,4
THERMAL CONDUCTIVITY (W/m·K)	0,032
REACTION TO FIRE	F
SOUNDPROOFING IN DOWNSPOUTS (R;dBA)	12*
DIMENSIONS (m)	5,5 x 1
m ² / PALLET	66
STORAGE: The material must be kept from weather and stored upright.	

* Theorist calculation

RECOMMENDED FOR...

- Soundproofing of all types of piping, both air and water.
- Slab soundproofing reinforcement.